



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Volvo.

| Product name  | Description   | Specifications             | Approvals                      | FUCHS Recommendations                               |
|---|---|----------------------------|--------------------------------|---|
| <b>Engine Oils</b>  |   |                            |                                |   |
| <b>TITAN<br/>GT1 PRO V<br/>SAE 0W-20</b><br><br>     | Premium Performance Engine Oil with new XTL-Technology in ground-breaking viscosity class. Specially designed for modern VOLVO vehicles, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. | –                          | VOLVO VCC<br>RBS0-2AE          | ACEA A1/B1  |
| <b>TITAN<br/>SUPERSYN FE<br/>SAE 0W-30</b>  | Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption.   | ACEA A5/B5                 | VOLVO VCC<br>95200377          | –   |
| <b>TITAN<br/>SUPERSYN<br/>SAE 5W-40</b>   | Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.  | ACEA A3/B4                 | –                              | –   |
| <b>Gear Oils</b>  |   |                            |                                |   |
| <b>TITAN<br/>SINTOFLUID FE<br/>SAE 75W</b><br><br> | Premium Performance Manual Transmission Fluid offering increased efficiency in passenger cars due to its low viscosity and can also be used in reducer gearboxes of hybrid vehicles. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.     | API GL-4                   | -                              | -   |
| <b>TITAN<br/>SINTOFLUID<br/>SAE 75W-80</b>  | Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.  | API GL-4                   | –                              | VOLVO 97308   |
| <b>TITAN<br/>SINTOPOID FE<br/>SAE 75W-85</b>  | Premium Performance fuel-economy passenger car axle fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.  | API GL-5                   | –                              | –   |
| <b>TITAN<br/>SINTOPOID LS<br/>SAE 75W-90</b>  | Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.  | API GL-4/-5/-5<br>inkl. LS | –                              | –   |
| <b>TITAN<br/>SUPERGEAR MC<br/>SAE 80W-90</b>  | Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.  | API GL-4/GL-5              | –                              | VOLVO 97310   |
| <b>Automatic Transmission Fluids (ATF)</b>  |   |                            |                                |   |
| <b>TITAN<br/>ATF 6400</b><br><br>                  | Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.                        | –                          | DEXRON VI<br>FORD MERCON<br>LV | AISIN WARNER/<br>AW-1                               |
| <b>TITAN<br/>ATF 4400</b>   | Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.  | –                          | –                              | DEXRON III<br>FORD MERCON<br>JWS 3309/TYP<br>E T-IV |

| Product name  | Description  | Specifications   | Approvals | FUCHS Recommendations  |
|---|--|--|-----------|--|
| <b>Central Hydraulic / Power Steering Fluids</b>  |  |  |           |  |
| <b>TITAN<br/>CHF 11S</b>  | Premium Performance TCF specially designed for use in many transfer cases with wet running clutch.   | –  | –         | VOLVO 1161529  |
| <b>TITAN<br/>CHF 202</b><br><br>         | Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers.<br>Product dyeing: green.                                       | –  | –         | VOLVO 30741424   |
| <b>Antifreeze</b>   |  |  |           |  |
| <b>MAINTAIN<br/>FRICOFIN LL</b>   | Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines, phosphates and silicates with OAT-technology. Product dyeing: orange.                                  | ASTM D 3306<br>TYPE I  | –         | VOLVO COOLANT<br>VCS (STD 418-0001)<br>VOLVO COOLANT<br>XLC (STD 418-0005) |
| <b>MAINTAIN<br/>FRICOFIN 50</b>   | Premium Performance Coolant Ready-Mix based on monoethylene glycol. Free of nitrites, amines and phosphates with hybrid technology. Offers frost protection down to -37°C. Product dyeing: blue-green. | ASTM D 3306<br>TYPE III  | –         | –  |
| <b>Brake Fluids</b>   |  |  |           |  |
| <b>MAINTAIN<br/>DOT 514 LV</b><br><br> | Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.  | FMVSS NR.<br>116 DOT<br>3/4/5.1<br>ISO 4925<br>CLASS 3/4/5-<br>1/6/7<br>JIS K2233<br>CLASS 3/4/5/6<br>SAE J<br>1703/1704 | –         | –  |
| <b>MAINTAIN<br/>DOT 4 HT</b>  | Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.  | FMVSS NR.<br>116 DOT 3/4<br>ISO 4925<br>CLASS 3/4<br>JIS K2233<br>CLASS 3/4<br>SAE<br>J1703/J1704                        | –         | –  |

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

**PARTNER**  
des deutschen Kraftfahrzeuggewerbes

