

LUBRICANTS FOR JAGUAR LAND ROVER PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Jaguar Land Rover.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 FLEX 5 SAE 0W-20 	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers such as Toyota or Mercedes-Benz.	ACEA C6, C5 API SN PLUS RC API SP RC	JAGUAR LAND ROVER STJLR.03.5006	JAGUAR LAND ROVER STJLR.51.5122
TITAN GT1 PRO C-1 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	–	JAGUAR LAND ROVER STJLR.03.5005	FORD WSS- M2C934-B
TITAN SUPERSYN F ECO-FE SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil especially developed for modern Ford Diesel engines. Excellent cold starting and lower oil consumption.	ACEA C2 FORD WSS- M2C950-A	JAGUAR LAND ROVER STJLR.03.5007	–
TITAN SUPERSYN F ECO-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines. Optimum cold starting and lower oil consumption.	ACEA C5 API SN FORD WSS- M2C948-B	JAGUAR LAND ROVER STJLR.03.5004	FORD WSS- M2C925-A FORD WSS- M2C925-B
TITAN SUPERSYN F ECO-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 API SL FORD WSS- M2C913-C FORD WSS- M2C913-D	–	FORD WSS- M2C913-A FORD WSS- M2C913-B JAGUAR LAND ROVER STJLR.03.5003 JAGUAR M2C913-B
Gear Oils				
TITAN SINTOFLUID FE 75W 	Premium Performance Manual Transmission Fluid offering increased efficiency in passenger cars due to its low viscosity and can also be used in reducer gearboxes of hybrid vehicles. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	FORD WSS- M2C200-D2
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	FORD WSS- M2C200-C/C2
TITAN SINTOPOID LS SAE 75W-140	Premium Performance Gear Oil for axle and transfer gearboxes, formulated with fully-synthetic base oils. Suitable for axle and transfer gearboxes with and without limited slip differential.	API GL-5	–	FORD WSL- M2C192-A
Double Clutch Transmission Fluids (DCTF)				
TITAN FFL-3 	Premium Performance DCTF. Specially developed for wet clutch ZF/Porsche DCTs. Additionally applicable in hybridized axle transmissions from Mercedes-Benz. Provides optimum wear protection and excellent friction properties even under hard conditions and offers best shifting performance over the whole lifetime.	–	–	JAGUAR LAND ROVER GX73- M1R564-AA
Automatic Transmission Fluids (ATF)				

LUBRICANTS FOR JAGUAR LAND ROVER PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN ATF 6400 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	–	DEXRON VI	AISIN WARNER/AW-1
TITAN ATF 6008 	Premium Performance ATF, specially developed to optimize the shifting performance of ZF automatic transmissions incl. hybrid applications. Product dyeing: green.	–	–	JAGUAR 02JDE 26444 LAND ROVER LR023288
TITAN ATF 6006	Premium Performance ATF, specially developed to optimize the shifting performance of ZF automatic transmissions. Product dyeing: none.	–	–	JAGUAR FLUID 8432 LAND ROVER TYK500050
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	DEXRON III (H)	FORD MERCON
Central Hydraulic / Power Steering Fluids				
TITAN CHF 11S	Premium Performance TCF specially designed for use in many transfer cases with wet running clutch.	FORD WSS-M2C204-A	–	–
TITAN CHF 202 	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	FORD WSS-M2C204-A2	–	LAND ROVER LR003401
Antifreeze				
MAINTAIN FRICOFIN LL	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines, phosphates and silicates with OAT-technology. Product dyeing: orange.	ASTM D 3306 TYPE I FORD WSS-M97-B44-D JAGUAR LAND ROVER STJLR.651.5003	–	–
Brake Fluids				
MAINTAIN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–
<p>The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022</p>				

LUBRICANTS FOR JAGUAR LAND ROVER PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
--------------	-------------	----------------	-----------	-----------------------

FUCHS LUBRICANTS GERMANY GmbH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

