

Product Information

MOVING YOUR WORLD



TITAN GT1 PRO C-3 SAE 5W-30

Premium Performance engine oil with new XTL® Technology. Excellent cold starting behaviour, very fast oil circulation, and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended oil drain intervals. Specifically developed for BMW, VW & Mercedes-Benz petrol and diesel vehicles with exhaust gas aftertreatment.

Description

TITAN GT1 PRO C-3 SAE 5W-30 is a Premium Performance engine oil for passenger cars and vans. The innovative XTL® Technology offers highest performance across the full operating temperature range from cold start to high-temperature operation. The unique lubrication properties of the XTL® Technology offer significant benefits in highly loaded engines, especially also in the latest downsized engines with or without stop-start systems. Engines with a high power density enjoy reliable lubrication and start easier and quicker. Due to its additive technology with reduced SAPS content (Sulphated Ash, Phosphor and Sulphur) TITAN GT1 PRO C-3 SAE 5W-30 protects exhaust gas aftertreatment systems and improves their durability. TITAN GT1 PRO C-3 SAE 5W-30 was developed to meet modern requirements; it is based on selected base oils and state-of-the-art additive technology. XTL® Technology is proven to allow lower fuel consumption even compared to oils of the same SAE-class.

Application

TITAN GT1 PRO C-3 SAE 5W-30 is suitable for vehicles running on petrol, diesel, or gas (LPG, CNG), and with modern exhaust gas aftertreatment systems. TITAN GT1 PRO C-3 SAE 5W-30 should only be used in diesel engines, when also low sulphur diesel fuel is used. TITAN GT1 PRO C-3 SAE 5W-30 is ideally suited for a large number of Asian and American manufacturers, as well as for many hybrid engines.

TITAN GT1 PRO C-3 SAE 5W-30 is miscible and compatible with conventional, branded engine oils. However, mixing with other engine oils should be avoided in order to fully exhaust this product's benefits. A complete oil drain is recommended when converting to TITAN GT1 PRO C-3 SAE 5W-30. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages

- Excellent cold start behaviour and fast oil circulation in the whole engine at low temperatures.
- The XTL® Technology resulted in an even further improved fuel economy compared to engine oils of the same viscosity grade.
- Extremely low oil consumption offered by XTL® Technology.
- Protects exhaust gas aftertreatment systems because of a low content of sulphated ash, phosphorus and sulphur (Low-SAPS).
- Excellent wear protection even under high loads.
- Significant reduction of residues in engines and turbochargers.
- Universally applicable for diesel, petrol and gas engines of a large number of manufacturers.
- Suitable for selected hybrid vehicles subject to OEM requirements.

Product Information

MOVING YOUR WORLD



Specifications

- ACEA C3
- API SN

Approvals

- BMW LONGLIFE-04
- MB-APPROVAL 229.51
- PORSCHE C30
- VW 504 00/507 00

FUCHS Recommendations

- CHRYSLER MS-11106
- FIAT 9.55535-S3
- MB 229.52

Product Information

MOVING YOUR WORLD



TYPICAL CHARACTERISTICS

Density at 15°C	DIN 51757	0.851 g/ml
SAE Grade	SAE J300	5W-30
Kinematic Viscosity at 40°C	DIN 51562-1	60 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	11.65 mm ² /s
Viscosity Index	DIN ISO 2909	192
HTHS	CEC L-36-90	≥ 3,5 mPa*s
Pour Point	DIN ISO 3016	-45 °C
Sulphated Ash	ASTM D874	≤ 0,8 % m/m
Product Dyeing	DIN 10964	none

Product Information

MOVING YOUR WORLD



Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.